2057687350

Effective Date:	6/30/95	
Supercedes:	11/23/94	

PRELIMINARY Specification for Philip Morris Converted Tipping Paper

Brand Code(s): #05300 / # 05370 (JPN) Bobbin Dimensions: 50 mm x 3500 M Base Sheet: KC GSR 757 M2 Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 cm ± 1.00 mm C. Distance Between Perforation Rows w/in Each Band 5 D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcool filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: XX A. Thorpe XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX S. Cline XX J. Ellis/D. Kelton /A. Milburn/K. Smith XX A. Thorpe XX	Brand(s):	Lark Milds KS Regular SP / FTB - TIOJ									
Brand Code(s): #05300 / # 05370 (JPN) Bobbin Dimensions: 50 mm x 3500 M Base Sheet: KC GSR 757 M2 Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Boles / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band 1.50 mm ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By:											
Brand Code(s): #05300 / # 05370 (JPN) Bobbin Dimensions: 50 mm x 3500 M Base Sheet: KC GSR 757 M2 Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Boles / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band 1.50 mm ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By:											
Brand Code(s): #05300 / # 05370 (JPN) Bobbin Dimensions: 50 mm x 3500 M Base Sheet: KC GSR 757 M2 Bobbin Dimensions: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands B. Perforation Band Width C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX			*								
Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Roles / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	Brand Code(s):	# 05	5300 / # 05	370 (JPN)							
Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Roles / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX			· · · · · ·							· · · · · · · · · · · · · · · · · · ·	
Bobbin Description: Cork T (WHT) L Unperforated Material Code: 11-611-A Converter: Mundet Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Roles / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	Dakkia Dimonsi			50 mm	v 2500 M	Rose	Sheet.	ĸc	GSR 751	7 M2	
Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm				CO. I DO ATTICIONAL T		Dasc			120 0010 / 0 / 11/2		
Perforated Material Code: 14-612-B Quantity: Location: Cabarrus Louisville Richmond XX Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm	-	-									
Louisville Richmond XX	Unperforated M	[ateria]	l Code:		11-611-A		Converter:		Mundet		
Louisville Richmond XX											
Louisville Richmond XX											
Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band 5 D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed:	Perforated Material Code:			14-612-B		Quantity	<u></u>		<u> </u>		
Perforation R.T.D.: 0.10 cm ± 0.05 cm Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band 5 D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed:	Location: Cab	jarrus			Louisville		Richn	aond	XX		
Number of Rows: two (2) Holes / Inch / Row: 35 To 45 A. Distance between Perforation Bands 28.00 mm ± 1.00 mm B. Perforation Band Width 1.50 mm ± 0.50 mm C. Distance Between Perforation Rows w/in Each Band ± 0.50 mm D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX											
A. Distance between Perforation Bands B. Perforation Band Width C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Paper Degree Sent Tipping Inventory NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: Edge of Paper Degree Sent Tipping Inventory NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: Edge of Perforation Rows w/in Each Band Edge of Tipping Paper 9.50 mm ± 1.00 mm Edge of Perforation Rows w/in Each Band Edge of Tipping Paper 9.50 mm ± 1.00 mm	Perforation R.T.	.D.:		0.10	cm	±	0.05	cm	_		
A. Distance between Perforation Bands B. Perforation Band Width C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Perforation Band to Edge of Tipping Paper Edge of Paper Degree Sent Tipping Inventory NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: Edge of Paper Degree Sent Tipping Inventory NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: Edge of Perforation Rows w/in Each Band Edge of Tipping Paper 9.50 mm ± 1.00 mm Edge of Perforation Rows w/in Each Band Edge of Tipping Paper 9.50 mm ± 1.00 mm	Number of Down			frago	(2)						
A. Distance between Perforation Bands B. Perforation Band Width C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	Number of Rows	s: _		two	(2)						
B. Perforation Band Width C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX	Holes / Inch / Ro	ow:		35	To	45	5				
C. Distance Between Perforation Rows w/in Each Band D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accomodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX							28.00 mm	<u>.</u> ± .	1.00 mm		
D. Edge of Perforation Band to Edge of Tipping Paper 9.50 mm ± 1.00 mm REPLACEMENT INSTRUCTIONS: XX						_	1.50 mm		0.50 mm		
REPLACEMENT INSTRUCTIONS: XX								0.50	_	1.00 mm	
Effective Immediately: (DO NOT USE UP PRESENT TIPPING INVENTORY NOW) Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX		Đ. I	Edge of Pe	erforation.	Band to Edge of '	Cipping Pa	per _	9.50 mm	± .	1,00 IIIII	
Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	REPLACEMEN	T INS	TRUCTI	ONS:					•		
Use Up Present Inventory is Exhausted Comments: Perforation target changed from 0.75 cm / 2 row ("A") model to 0.10 cm / 2 row to accommodate the conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: S. Rosen XX Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	YY Effective Immediately: (DO NOT HSE HD DRESENT TIPPING INVENTORY NOW)										
conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	727	_		-	•	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			,	
conversion from the plug-space-plug design and current blend to the dual-combined charcoal filter from AFC and the P98 Lark blend for Lark - Japan only. Must be simultaneous with the blend/filter change. Prepared by: E. W. Weston - Q&SE Approved By: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	Commenter Powering torget changed from 0.75 cm / 2 rary /"A"\ model to 0.10 cm / 2 rary to accompidate the										
Prepared by: E. W. Weston - Q&SE Approved By: Ell Meson Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	co	nversi	on from th	e plug-spac	ce-plug design and	current ble	nd to the di	ual-combine	d charcoa	l filter from	
Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	A	FC and	I the P98 I	ark blend	for Lark - Japan o	nly. Must b	e simultane	ous with the	blend/fil	ter change.	
Distributed: D. Fessel XX L. Craighill/A. Davis S. Rosen XX	Prepared by:		E. W. V	Weston - Q	&SE A _{ll}	proved By	ير	EU/1	rles		
D. Fessel XX L. Craighill/A. Davis S. Rosen XX						- •					
	Distributed:	D. I	Fessel	XX L.C	Craighill/A. Davis			\$. Re	osen	XX	
						Milburn/K.	Smith		_	XX	